


Werkstoff: Stahl verzinkt; bzw. Edelstahl rost- und säurebeständig



Werkstoff: Neopren; Temperaturbeständig bis 100 °C

### Schlauchklemmen, Stahl verzinkt

Bestell-Nr.	1.000.961.011	1.000.961.029	1.000.961.003	1.000.961.006	1.000.961.012	1.000.961.013	1.000.961.014	1.000.961.010	
für Gelenkgröße	0.716/0.816/ 0.720/0.820	0.824/0.725/ 0.828	0.732/0.832/ 0.836	0.740/0.840/ 0.845	0.750/0.850/ 0.855	0.860/0.865	0.870	0.880	
Spannbereich	mm	12 – 20	20 – 32	25 – 40	32 – 50	40 – 60	50 – 70	60 – 80	70 – 90

### Schlauchklemmen, Edelstahl, rost- und säurebeständig

Bestell-Nr.	1.000.961.020	1.000.961.022	1.000.961.023	1.000.961.024	1.000.961.025	1.000.961.026	1.000.961.027	1.000.961.028	
für Gelenkgröße	0.716/0.816/ 0.720/0.820	0.824/0.725/ 0.828	0.732/0.832/ 0.836	0.740/0.840/ 0.845	0.750/0.850/ 0.855	0.860/0.865	0.870	0.880	
Spannbereich	mm	12 – 20	20 – 32	25 – 40	32 – 50	40 – 60	50 – 70	60 – 80	70 – 90

### Faltenbälge

Bestell-Nr.	1.000.830.009	1.000.830.010	1.000.830.013	1.000.830.014	1.000.830.002	1.000.830.003	
für Gelenkgröße	0.716/0.816	0.720/0.820	0.725/0.824	0.828	0.732/0.832	0.836	
L	mm	40	47	52	58	67	74
D	mm	31	33	46	50	54	65
d	mm	16	20	25	28	32	36

1.000.830.004	1.000.830.015	1.000.830.016	1.000.830.006	1.000.830.007	1.000.830.017
0.740/0.840	0.845	0.750/0.850	0.855/0.860	0.865/0.870	0.880
84	97	110	122	132	157
75	82	90	100	110	131
040	45	50	56	65	80